

IPLI series

DATASHEET

Sensor Partners BV

📍 James Wattlaan 15
5151 DP Drunen
The Netherlands

☎ +31 (0)416 - 37 82 39

✉ info@sensorpartners.com

🌐 sensorpartners.com

Sensor Partners BVBA

📍 Z.1 Researchpark 310
B-1731, Zellik
Belgium

☎ +32 (0)2 - 464 96 90

✉ info@sensorpartners.com

🌐 sensorpartners.com

DC - CYLINDRIC TYP: IPLI0814 / PNP NO

Configuration:	M8
Fitting:	non-flush
Sensing Distance Sn (mm):	2,0 mm
Connection:	pluggable M12
Nominal Voltage:	24 VDC
Voltage Range:	10-30 VDC
max. Load Current:	200 mA
No-Load Current:	< 15 mA
Voltage Drop:	< 2 V
Switching Frequency:	5 kHz
Hysteresis:	< 15 % (Sr)
Reproduceability:	< 1 % (Sr)
Temperature Drift:	< 10 % (Sr)
Ambient Temperature:	-25 Å°C ... +70 Å°C
Protection Class:	IP 65
Short Circuit- /Inverse Polarity Protection:	yes
Housing Material:	Brass nickel plates
LED:	yes
Connection:	Plug M12
Material Active Surface:	
EMC:	
Shock/Vibration:	

